

### **SLK Series**



#### **Shur-Lok Access Doors**

**Doors** are designed for drywall, masonry or concrete construction and provide the security required in today's schools, hospitals, hotels, and correctional institutions.

**Door Panel** are fabricated from 14 gage, galvannealed steel and the door is provided with a 16 gage vertical reinforcement channel.

**Frame** is fabricated from 16 gage, galvannealed steel.

**Lock** is an automatic springbolt type featuring a precision mechanism. When the door is closed in the locked position, the uniquely designed angled cam lock automatically engages. The key can only be removed when the lock is in the locked position.

**Hinge** is a concealed continuous stainless steel piano hinge

**Finish** is a white prime coat suitable for painting.

### **Guide Specification**

Provide Elmdor® SLK Series, Shur-Lok Access Doors (specify model number and options). Access door panel shall be fabricated from 14 gage, galvannealed steel with a white prime coat finish. Frame is fabricated from 16 gage, galvannealed steel with a white prime coat finish. Door shall have a 16 gage vertical reinforcement channel, a concealed hinge, and an automatic locking, spring bolt lock. Finish shall be a white prime coat suitable for painting.







# MODEL NUMBER AND OPTIONS SELECTION

#### **BASE MODEL NUMBER**

☐ SLK Shur-Lok Access Door

## **Suffix Options**

☐ -AS Automatic Spring Door Closer
Stainless Steel Construction
(Type 304 No. 4 Satin Finish)


## STANDARD AVAILABLE SIZES


Special sizes available upon request.

and the second s				
NOMINAL DOOR SIZE (W X H)	WALL OPENING (minimum required)	KEY QTY	WEIGHT	-SDL (Extra Latches)
SLK 8" x 8"	8-1/2" x 8-1/2"	1	4 lbs.	0
SLK 10" x 10"	10-1/2" x 10-1/2"	1	5.5 lbs.	0
SLK 12" x 12"	12-1/2" x 12-1/2"	1	7 lbs.	0
SLK 14" x 14"	14-1/2" x 14-1/2"	1	8 lbs.	0
SLK 16" x 16"	16-1/2" x 16-1/2"	1	10 lbs.	0
SLK 18" x 18"	18-1/2" x 18-1/2"	1	12 lbs.	2
SLK 18" x 24"	18-1/2" x 24-1/2"	1	16 lbs.	4
SLK 22" x 22"	22-1/2" x 22-1/2"	1	17.5 lbs.	2
SLK 24" x 24"	24-1/2" x 24-1/2"	1	20.5 lbs.	2
SLK 24" x 30"	24-1/2" x 30-1/2"	1	24 lbs.	4
SLK 24" x 36"	24-1/2" x 36-1/2"	1	28 lbs.	6
SLK 30" x 30"	30-1/2" x 30-1/2"	1	28.5 lbs.	6
SLK 36" x 36"	36-1/2" x 36-1/2"	1	41.5 lbs.	8

## Notes:

- 1. Concealed Hinge
- 2. Door
- 3. Reinforcement Channel
- 4. Spring Door Lock
- 5. SDL (Extra Latches) Big Doors Only





MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Dimensions are subject to manufacturer's tolerance of plus or minus 1/4". Elmdor/Stoneman assumes no responsibility for use of void or suspended data. Please visit **www.elmdorstoneman.com** for most current specifications. © Copyright 2009 Elmdor/Stoneman, City of Industry, CA, A Division of Acorn Engineering Company.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING					
Model Number & Options	Quantity				
Company	Date				
Contact	Title				
Approval for Manufacturing/Signature					

**SLK** Revised: 08/31/18